

STRIPPER

Paint remover

White

SUBSTRATE

Polyester | GRP | Wood | Aluminium | Steel



3m²/L



DESCRIPTION

STRIPPER is a stripping gel based on Watertech® technology. This stripper impregnates and softens antifouling layers and single-component paints. This stripper is harmless to GRP, as it contains neither acid nor base. Tinted white, it gives a clear view of the areas covered.

MAIN FEATURES

COVERAGE	3m ² /L per layer
FLASH POINT	FP > 60°C
UNIT SIZE	5L
TYPICAL SHELF LIFE	5 years
CLEANING	With water

APPLICATION

- Shake the jar well before use to break up the gel and homogenise the product.
 - Wash the surface with detergent, rinse with fresh water and leave to dry.
- For antifouling, we recommend cleaning the hull thoroughly with a high-pressure cleaner and scrubbing the surface with a P40 while it is still damp.
- Apply a very thick coat with an upholstery brush. Proceed in strips of around 1 to 2m². The thickness applied is sufficient when you can no longer see the substrate.
 - Wait 30 to 45 minutes, then remove the dissolved paint with a spatula, collecting the residue in a container.
 - Clean the stripped surface with a cloth soaked in DA thinner.
 - Polish with P120 before applying new paint.

Tip: Stripping the hull is easy if carried out every 2-3 years.

INFORMATIONS

OPERATOR PROTECTION

- Paint for amateur and professional use.
- Before use, read this sheet, the label and the product information carefully.
- Work in a well-ventilated area, wear protective clothing, gloves, goggles and a suitable mask.

TRANSPORT AND STORAGE

- The product must be transported and stored in hermetically sealed containers that are not permeable to solvents.
- Do not expose to the open air, sunlight or extreme temperatures. To keep the product in good condition, recap the can after use, turn the jars upside down and store between 10°C and 25°C. Do not expose to sunlight.

WASTE

- Empty cans and soiled waste must be disposed of in accordance with current municipal regulations on the treatment of hazardous products, for example by taking them to a waste collection centre or using dedicated bins. Do not dispose of waste in drains or waterways. Use the bins provided. It is advisable to allow paint residues to harden before disposing of them.

GENERAL

- The information given in this data sheet is not exhaustive. Anyone using this product for purposes other than those recommended, without prior written confirmation from us as to the feasibility of such use, does so at their own risk. Nautix cannot be held responsible. This information is subject to change without notice.