

MARINE PAINTS

# NAUTIX

## TECHNICAL DATA SHEET

### DE

Thinner for epoxy primer and finish



#### SUBSTRATE

Polyester | Wood | Steel



## DESCRIPTION

DE Thinner can be used with all epoxy paints. It is particularly recommended for facilitating application and cleaning tools. DE can be used in particular with PE, HPE and EPOXYGARD epoxy primers. It can also be combined with U2 undercoat or NX194 finish.

## MAIN FEATURES

FINISH	<b>Translucent</b>
FLASH POINT	<b>FP &gt; 36°C</b>
UNIT SIZE	<b>0,75L – 2,5L</b>
TYPICAL SHELF LIFE	<b>5 years</b>
SPECIFICATION	<b>Ready for use</b>

## APPLICATION

#### BRUSH/ROLLER

- Dilution up to 10% (by volume)

#### AIRMIX SPRAY

- Dilution of 15 to 25% (by volume)

#### AIRLESS SPRAY

- No dilution or 5% maximum (by volume)

#### SPECIAL ADVICE

Thinning considerably increases the drying time before recoating.

When diluting heavily, apply thinly to allow the solvents to evaporate quickly.

Do not dilute more than 25%, as this may damage the technical properties of the paint, causing the film to break or premature fouling.

## INFORMATIONS

#### OPERATOR PROTECTION

- Paint for amateur and professional use.
- Before use, read this sheet, the label and the product information carefully.
- Work in a well-ventilated area, wear protective clothing, gloves, goggles and a suitable mask.

#### TRANSPORT AND STORAGE

- The product must be transported and stored in hermetically sealed containers that are not permeable to solvents.
- Do not expose to the open air, sunlight or extreme temperatures. To keep the product in good condition, recap the can after use, turn the jars upside down and store between 10°C and 25°C. Do not expose to sunlight.

#### WASTE

- Empty cans and soiled waste must be disposed of in accordance with current municipal regulations on the treatment of hazardous products, for example by taking them to a waste collection centre or using dedicated bins. Do not dispose of waste in drains or waterways. Use the bins provided. It is advisable to allow paint residues to harden before disposing of them.

#### GENERAL

- The information given in this data sheet is not exhaustive. Anyone using this product for purposes other than those recommended, without prior written confirmation from us as to the feasibility of such use, does so at their own risk. Nautix cannot be held responsible. This information is subject to change without notice.