

GRIP ADDITIVE

Non-slip compounds

Medium grade or Coarse grade

SUBSTRATE

Polyester | GRP | Metal



DESCRIPTION

GRIP ADDITIVE is an anti-slip compounds to be added to topcoats or varnishes, whether single- or two-component. The selection of specific grains promotes foot adhesion on wet surfaces. The Medium finish is reserved for decks, while the Coarse finish is recommended for high-traffic areas or areas requiring a high level of grip, such as the cockpit. Thanks to their lightweight formulation, Nautix non-slip powders do not clump at the bottom of the container during mixing.

MAIN FEATURES

UNIT SIZE	Medium : 100g - 250g Coarse : 100g - 250g
TYPICAL SHELF LIFE	5 years
SPECIFICATION	For use in topcoats or varnishes

APPLICATION

- Preparation: the surface must be degreased with Nautix SD, then sanded with 80–120 grit, and thoroughly dusted off.
- Select the type of paint and follow the mixing ratio in the table.
- Stir well before use and allow to debubble if necessary

ROLLER

- Apply an even coat using the special «primer and anti-slip» roller, criss-crossing for a perfect finish. Do not «pull» the paint for better durability.
- Follow the application instructions for the topcoat or additive varnish.

AIRLESS SPRAY

- 2 bar, nozzle 2.5-3.0mm

INFORMATIONS

OPERATOR PROTECTION

- Paint for amateur and professional use. Dangerous product.
- Before use, read this sheet, the label and the product information carefully.
- Work in a well-ventilated area, wear protective clothing, gloves, goggles and a suitable mask.

TRANSPORT AND STORAGE

- The product must be transported and stored in hermetically sealed containers that are not permeable to solvents.
- Do not expose to the open air, sunlight or extreme temperatures. To keep the product in good condition, recap the can after use and store between 10°C and 25°C.

SAFETY

- Read the label and product information before use. Observe the precautions for use. Carefully read the safety advice given in the Health and Safety section, which is also available from Nautix and its retailers.
- All professional operators must wear appropriate protective clothing: coveralls in a colour that contrasts with the product being applied, disposable hooded under-suits, appropriate gloves and protective footwear that protects the lower limbs. Wear a respirator when spraying.

WASTE

- Empty cans and soiled waste must be disposed of in accordance with current municipal regulations on the treatment of hazardous products, for example by taking them to a waste collection centre or using dedicated bins. Do not dispose of waste in drains or waterways. Use the bins provided. It is advisable to allow paint residues to harden before disposing of them.

GENERAL

- The information given in this data sheet is not exhaustive. Anyone using this product for purposes other than those recommended, without prior written confirmation from us as to the feasibility of such use, does so at their own risk. Nautix cannot be held responsible. This information is subject to change without notice.

MEDIUM MIXING RATIO

100g GRIP for 1L varnish VA2
140g GRIP for 1L topcoat STARLAC
120g GRIP for 1L topcoat L2

HARD MIXING COARSE

Mixing ratio to be adjusted according to the desired level of adhesion.

Between 80 and 100g GRIP for 1L varnish VA2
Between 110 and 140g GRIP for 1L topcoat STARLAC
Between 100 and 120g GRIP for 1L topcoat L2